

ADD: No.777, East Changzhi Road, Hongko District, Shanghai, CHINA

TEL : +86 21 65370008 FAX : +86 21 65370078 MOB: +86 13775219101 Email: bruce@spreadsun.com

U-Type Solar Collector

Main Specifications :

- 1) Inner manifold: Main pipe of U-type tubes: 22*0.8mm, branch pipe of U-type tubes: 8*0.6mm
- 2) Vacuum tube: AIN/AIN-SS/CU coating 58-1800mm or 47-1500mm
- 3) Outer manifold: Stainless steel SUS 304 0.8mm thickness/Aluminum alloy 2.0mm thickness
- 4) insulation: insulation: Rock wool or polyurethane
- 5) Frame: Stainless steel SUS 201-1.2mm/Aluminum alloy 2.5mm, 2mm
- 6) Inlet&outlet: 22mm
- 7) Working Pressure : $\leq 1.0\text{Mpa}$



Optional Part :

- 1) Reflector: aluminum component/stainless steel (add \$0.6/tube)

Model	Light Area(m ²)	Vacuum Tube			FOB Price(USD)	
		Ø(mm)	L(mm)	Qty (pcs)	FLAT	SLOPE
SGRB D 581810	1.4	58	1800	10	130	125
SGRB D 581812	1.68	58	1800	12	155	150
SGRB D 581815	2.1	58	1800	15	190	185
SGRB D 471510	0.9	47	1500	10	115	110
SGRB D 471512	1.08	47	1500	12	140	130
SGRB D 471515	1.35	47	1500	15	170	155
SGRB D 471518	1.62	47	1500	18	200	185
SGRB D 471520	1.8	47	1500	20	225	205